

GENERIC

MKR-401AU-D 4Port Auto Desktop KVM Switch PS/2



SPECIFICATIONS:

Model	MKR-401AU-D
Description	4PCs or Servers to 1 User
Daisy-chain	32units/128PCs
Auto Scan	Yes
Manual Control	Yes
Hot Key Control	Yes
Support Computer Or Server	4PCs IBM PS/2 Compatible
Support Monitor	VGA (SVGA,XGA,Multisync) Monitor (General or PNP) Maximum Resolution:1600 x 1200 Video Bandwidth : 200MHz Horizontal Frequency : 30 - 100KHz Vertical Frequency : 43 - 120Hz
Support Keyboard	PS/2
Support Mouse	PS/2
PC Side Connector	HD-15Fx4/ MD-6F x4
Console Connector	HD-15F x1/ MD-6F x2
Daisy-chain Connector	HD-15F x1/ MD-6F x2
Scan Rate	5 sec / 10 sec.
Time Out	30 sec. / 60 sec.
Transmission Distance	Computer to KVM : 35 meters Console Side to KVM : 50meters
Case Design	Desk-top
Dimension (L x W x H)	254 x 180 x 74 mm
Enclosure	Metal
Power Supply	DC 12.5VA

Specifications are subject to change without prior notice with advancement in technology.