

BSR31363U24

24Port 10/100Mbps Rack Mount Auto-MDI-X Switch



FEATURES:

- Compiles with the IEEE802.3 10 Base-T Ethernet
- And IEEE802.3u 100Base-TX Fast Ethernet standard.
- 24 port 10/100Mbps TX Auto-Negotiation Ethernet switch.
- Full/Half-Duplex capability on every TX port.
- Automatic Source MAC Address Learning and Aging.
- Supports TP interface Auto MDIX Function for auto TX/RX swap.
- Supports Store & Forward architecture and performs forwarding and filtering.
- Broadcast Storming Filter function.
- IEEE802.3x flow control for Full-duplex operation.
- Back Pressure function for Half-duplex operation.
- Runt and CRC Filtering eliminates erroneous packets to optimize the network bandwidth.
- Support to handle up to 1522 bytes packet.
- LED indicators for simple diagnostic and management.
- Internal power Supply.
- Plug and play.

SPECIFICATION:

Physical Characteristics

Port	24 10/100Mbps STP/RJ-45 Auto MDI-X ports,
Dimensions	432mm(L) x 220mm(W) x 44mm(H)
Input Power	100-240 VAC, 50/60 Hz Auto Sensing.
Filter & Forwarding Rate	Full Line Speed.
Transmission method	Store-and-forward
Buffer Memory	1522 Bytes.
LED Display	System Power LED. Individual port link/activity and speed LEDs

Standards Conformance

Environmental Temperature	Operating 0°C to 50°C Storage -20°C to 70°C
Humidity	Operating 10 % to 90 % RH Storage 5 % to 90 % RH
Standards	IEEE802.3 (10Base-T Ethernet) IEEE802.3u (100Base Fast Ethernet)

Specifications are subject to change without prior notice with advancement in technology.