

## BK707T+707R

### BayLan 2Port KVM Extender Switch PS2



#### FEATURES

- Provide best resolution: with a screwdriver to adjust the image on the right side where there's a cavity shown Focus for each receiver set.
- Easily plug & play operation - no tools required & just plug in the cables.
- VGA, SVGA, & Multi-sync monitor support
- Suitable for standard PS/2 computer or USB computer via USB adapter (PS121).
- Dual console operation - control your system from either the local or remote console.
- Combined with 2-output video splitter.
- Connect the transmitter and remote site via category 5 Ethernet cable, up to 180/330m.
- VGA resolution - 1000 ft (50MHz), 500 ft (125MHz).
- Supports monitor DDC function. (Display Data Channel)
- Receiver's console can manage receiver's computer or transmitter's.
- Each PC port can cascade other KVM switches.
- Hot Key function available.

#### SPCIFICATIONS

Technical Specifications		
Model	Transmitter BK707T	Receiver BK707R
<b>Connector</b> Unit to Unit VGA-In VGA-Out Keyboard Mouse	RJ-45 DB-15P male x 1 Black DB-15P male x 1 Blue PS/2 PS/2	RJ-45 DB-15P male x 1 Black DB-15P male x 1 Blue PS/2 PS/2
<b>LEDs</b>	PC x 1 Link x 1 Console Select x 1	PC x 1 Link x 1 PC Select x 1
<b>VGA Resolution</b>	125MHz at 500ft / 50MHz at 1000ft	125MHz at 500ft / 50MHz at 1000ft
<b>Cable Type</b>	CAT 5	CAT 5
<b>Power</b>	AC 9V/ 1000mA	AC 9V/ 1000mA
<b>Signal Type</b>	VGA, SVGA, XGA, & Multi-sync Monitor Support	VGA, SVGA, XGA, & Multi-sync Monitor Support
<b>Housing</b>	Metal	Metal
<b>Dimension (mm)</b>	L132* W79* H32mm	L132* W79* H32mm

Specifications are subject to change without prior notice with advancement in technology.