

BCR3X3112UC4A

BayLan Media Converter 10/100Base-TX to 10/100Base-FX Singlemode Simplex 25KM (1310nm)

FEATURES

- One-channel media conversion between 10/100Base-TX and 10/100Base-FX
- Fiber media allow: Single mode fiber using SC connector;
- Link Pass Through Function
- Auto negotiation of simplex mode on TX port
- Auto MDI/MDI-X for TX Port
- Full write-speed forwarding rate
- Front Panel status LEDs
- Used as a status-alone device or with a chassis
- Hot-Swappable when used with a chassis



SPECIFICATIONS

Applicable Standards	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX
Power Consumption	5.5 Watts (Maximum)
Speed	10/20Mbps for Half/Full-Duplex 100/200Mbps for Half/Full-Duplex
Media Interface	2 RJ-45, 1 SC
Forwarding Rate	148,800pps
Simplex Mode	Simplex Mode
Cable	10 Base-T 2-pair UTP Cat.3,4,5 UTP TO 100m (328ft) 10/100 Base-TX 4 Pair Cat. 5, EIA/TIA-568 100-ohm screen twisted-Pair(STP), up to 100m 10/100 Base FX 62.5/125µm multi-mode fiber optic cable, up to 2Km 9/125µm single-mode fiber optic cable up to 25 km
Weight	400g
Input Power	100 ~ 240VAC, 50/60 Hz
Dimensions	L95 x W70 x H25 mm
Operating Temperature	-0°C~ 70°C
Storage Temperature	-10°C ~70°C
Humidity	10~90%, non-condensing
Emissions	FCC part 15 Class A, CE Mark

Specifications are subject to change without prior notice with advancement in technology.