

BCR3X3112UC4A BayLan Media Converter 10/100Base-TX to 10/100Base-FX Singlemode Simplex 25KM (1310nm)

FEATURES

- One-channel media conversion between 10/100Base-TX and 10/100Base-FX
- Fiber media allow: Single mode fiber using SC connector;
- Link Pass Through Function
- Auto negotiation of simplex mode on TX port
- Auto MDI/MDI-X for TX Port
- Full write-speed forwarding rate
- Front Panel status LEDs
- Used as a status-alone device or with a chassis
- Hot-Swappable when used with a chassis



SPECIFICATIONS

| | |
|------------------------------|--|
| Applicable Standards | IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX |
| Power Consumption | 5.5 Watts (Maximum) |
| Speed | 10/20Mbps for Half/Full-Duplex 100/200Mbps for Half/Full-Duplex |
| Media Interface | 2 RJ-45, 1 SC |
| Forwarding Rate | 148,800pps |
| Simplex Mode | Simplex Mode |
| Cable | 10 Base-T 2-pair UTP Cat.3,4,5 UTP TO 100m (328ft) 10/100 Base-TX 4 Pair Cat. 5, EIA/TIA-568 100-ohm screen twisted-Pair(STP), up to 100m 10/100 Base FX 62.5/125µm multi-mode fiber optic cable, up to 2Km 9/125µm single-mode fiber optic cable up to 25 km |
| Weight | 400g |
| Input Power | 100 ~ 240VAC, 50/60 Hz |
| Dimensions | L95 x W70 x H25 mm |
| Operating Temperature | -0°C~ 70°C |
| Storage Temperature | -10°C ~70°C |
| Humidity | 10~90%, non-condensing |
| Emissions | FCC part 15 Class A, CE Mark |

Specifications are subject to change without prior notice with advancement in technology.