

PRP-076-NIU

BayLan 9Pin Impact Dot Matrix Printer (76mm)

USB Interface



Optional Ribbon

002296 RIBDM76

FEATURES

- Support Cash Drawer connection
- Compact and reasonable structure, easy maintenance design
- Built-in Data Buffer
- Built-in paper sensor automatically loading paper roll
- Characters can be enlarged bold underlined spaces between characters and lines can be adjusted
- Support different density BMP and download images printing
- Support black mark positioning printing
- Compatible with ESC/POS commands character front and columns are optional (using DIP switches)

Specifications are subject to change without prior notice with advancement in technology.

SPECIFICATIONS

Print Method	9pins impact Dot Matrix
Print Width	63.5mm
Print Resolution	400 dot/line
Columns	Font A: 33 columns or 35 columns Font B: 40 columns or 42 columns Simplified/Traditional: 21 columns or 22 columns
Print Speed	4.5line/sec max.
Interface	USB (Virtual COM)
Paper Diameter	75mm
Line Space	4.23mm(can be adjusted by sending commands)
Characters	ANK Font A: 9x9dots / Font B: 7x9dots Simplified/Traditional: 16 columns or 16 columns
Code Page	PC437 / Katakana / PC850 / PC860 / PC865 /West Europe/ Greek / Hebrew / East Europe /Iran /WPC1252 / PC866 / PC852 / PC858 / IranII / Latvian / Arabic / PT151,1251 / PC737 / WPC1257 / Thai Vietnam / PC864 / PC1001 / (Latvian) / (PC1001) / (PT151,1251) / (WPC1257)/ (PC864) / (Vietnam) / (Thai)
Barcode Type	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) CODABAR / ITF / CODE39 / CODE93 / CODE128
Fonts	GB2312
Buffer Data	4K bytes
Cash Drawer Output	DC 24V/1A
Power Supply	Input: AC 100-240V Output: DC 24V 2.5A (Built-in power adapter)
Mechanism	10million lines
Environment	Operating : 0°C ~ + 45°C , 10%RH ~ 80% RH Storage : -10°C ~ + 60°C , 10%RH ~ 90% RH
Dimensions (mm)	240(L) x 155(W) x 130(H)
Weight	2.5KG

Specifications are subject to change without prior notice with advancement in technology.