



The Brightest Choice of Networking & Communication

## PRP-058II-NU

### BayLan Thermal Receipt Printer 58mm Dia USB Interface



#### FEATURES

- User friendly, easy to install paper reel
- Maximum label width: 57.5mm  $\pm$  0.5mm
- Effective print width: 48mm
- Print speed: 90mm/sec
- Print density: 384 dots/line or 8 dots/mm
- Print head life 50km
- Halt-on protect function for over heat
- Cash drawer connection port
- ESC/POS print commands set

Specifications are subject to change without prior notice with advancement in technology.



The Brightest Choice of Networking & Communication

## SPECIFICATIONS

Print Width	48mm
Paper Width	384 dot/line
Print Speed	90mm/sec max.
Paper Width	57.5±0.5mm
Paper Diameter	Φ83mm
Columns	Font A:32 columns Font B:43 columns Simplified/Traditional: 16 columns
Interface	USB (Virtual COM)
Line Space	3.75mm(can be adjusted by sending commands)
Characters Size	ANK Font A:12x24dots / Font B:9x17dots Simplified/Traditional: 24 x 24 dots
Code Page	PC437 / Katakana / PC850 / PC860 / PC865 /West Europe/ Greek / Hebrew / East Europe /Iran /WPC1252 / PC866 / PC852 / PC858 / IranII / Latvian / Arabic / PT151,1251 / PC737 / WPC1257 / Thai Vietnam / PC864 / PC1001 / (Latvian) / (PC1001) / (PT151,1251) / (WPC1257) / (PC864) / (Vietnam) / (Thai)
Barcode Type	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) CODABAR / ITF / CODE39 / CODE93 / CODE128
Fonts	GB2312
Buffer Data	4K bytes
NV Flash	60K bytes
Cash Drawer	DC 12V/1A
Power Supply	Input: AC 100-240V Output: DC 8.5V 2.5A (Built-in power adapter)
Mechanism	50KM
Environment	Operating : 5°C ~ 45°C , 10%RH ~ 80% RH Storage :-10°C ~ 50°C , 10%RH ~ 90% RH
Dimensions (mm)	222(L) x 140(W) x 120(H)
Weight	1.5KG

Specifications are subject to change without prior notice with advancement in technology.