
EC-300
Barcode Handheld Laser Scanner



FEATURES

Plug-and-play universal cable; intuitive scanning

Scanning Mode: Manual

Durable construction: Designed for continuous usage all day, every day; significantly reduces downtime and repair costs.

High performance 1D liner scanner: Accurate first time scanning; always ready for the next scan; increased productivity resulting in shorter check-out lines.

Hands-free Intellistand: Enables presentation scanning and easy switching between hands-free and handheld modes

Specifications are subject to change without prior notice with advancement in technology.

Physical Characteristics

Dimensions:	16.8cm H x 6.8cm W x 9.0cm
Weight:	180gm
Voltage:	5 volts $\pm$ 10% 50mA, 30mA Standby
Color:	Black

Performance Characteristics

Scanner Type:	Bi-directional
Light Source:	650nm visible laser diode
Scan Rate:	200 scans per second
Print Contrast:	Above 30% Black
Decode Capability:	UPC/A, UPC/E, EAN-13/JAN-13, EAN-8/JAN-8, Code 39, Codabar, Interleaved 2 of 5, Code 93, MSI/PIESSEY, UK/PLESSEY, Code 11, Chinese 2 of 5, UPC/EAN128, China Postage, ISBN/ISSN.
Interface Supported:	USB
Scan Depth of Field:	0-750mm
Scan Distance:	upto 1M

User Environment

Operating Temp:	-20° to 60° C
Storage Temp:	30° to 90° C
Humidity:	5% to 95% relative humidity, noncondensing
EMI Emission:	FCC Class A
Shock Resistance;	1.8meter drop to concrete

Specifications are subject to change without prior notice with advancement in technology.