

POS80-30011BW

Thermal Receipt Printer USB+Serial+WIFI Dia 80mm/sec with Cutter, Vertical & Wall Mount (Black)



Features:

- Audible and visual alarm supported, best application for kitchen menu printing.
- USB port, WIFI Port, Serial port, and Ethernet interface integrated on a main board.
- It can be used for all kinds of commercial in retail POS systems, Restaurant system, and Industrial control systems
- Light weight and portable
- Beautiful shape
- Low cost and High-quality thermal printing
- Cash drawer drive supported
- Easy paper-roll installation, Easy maintenance and Rational structure
- Low-power waste, low-run cost (without the ribbons, ink cartridges)
- Built-in data buffers (be capable of receiving print data while printing)
- Characters can be amplified, printed in bold optionally, and line spacing printing can be adjusted
- Support different density bitmap graphics printing
- Support NV image downloading and printing
- Support raster bitmap printing
- High-speed printing using embedded soft font for all interfaces.
- Compatible with ESC/POS print instruction set, optional columns and font (Adjusted by DIP switch)
- Support Android OS (SDK on request)
- Support iOS (SDK on request)
- Support Window 8 OS

Specifications are subject to change without prior notice with advancement in technology.



The Brightest Choice of Networking & Communication

Print Method	Thermal Line Printing
Protocol	802.11b/g
Print Parameters	Support to Download the Logo Trademark
Print Speed	220mm/sec. (max)
Character Size	8 dots/line, 512 dots/line Font A: 12*24dots, 1.5(W)*3.0(H)mm Font B: 9*17dots, 1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)
Printing Chinese Characters	Traditional (complex font) Chinese: simplified Chinese 24x24 point, support 18030 font library, Support Taiwan and HK
ANK	ANK characters 12 x 24
Extended Character Table	OEM437 / KATAKANA / OEM850 / OEM860 / OEM863 OEM865 / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / OEM866 / OEM852 / OEM858 / IranII / Latvian / Arabic / PT1511251 / OEM747 / WPC1257/ Vietnam / OEM864 / Hebrew / WPC1255 /Thai
Paper Width	79.5mm ± 0.5mm (Print width 72mm)
Paper Reel Diameter	83mm
Paper Thickness	0.06 ~ 0.08mm
Interface	WIFI+Serial+USB (Virtual COM)
Power Supply	Input: AC 100-240V Output: DC 24V 2.5A 60W (Built-in power adapter)
Driver	Win9X / Win2000 / Win2003 / Win Vista / Win 7/ Window XP / Win 8 / Linux / Android Compatible with EPSON and SAMSUNG
Barcode Type	UPC-A / UPC-C / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) CODABAR / ITF / CODE39 / CODE93 / CODE128
Auto-Cutter	Full or Partial
Thermal film(Reliability)	100KM
Environment	Operating : 0°C ~ + 45°C , 10%RH ~ 80% RH Storage : -10°C ~ + 60°C , 10%RH ~ 90% RH
Dimensions	195(W) x155(H) x145(D)
Weight	1.60KG

Specifications are subject to change without prior notice with advancement in technology.