

BCR3X112UC2

BayLan Media Converter 10/100Base-TX to 10/100Base-FX Singlemode Simplex 20KM (Pair)

- 1310nm (Transmitter)
- 1550nm (Receiver)

FEATURES

- Single channel media conversion between 10/100Base-TX and 10/100Base-FX
- Fiber media allow Single mode fiber using SC connector
- Link Pass Through Function
- Auto MDI/MDI-X for TX Port
- Full write-speed forwarding rate
- Front Panel status LEDs
- Used as a status-alone device or with a chassis



SPECIFICATIONS

Applicable Standards	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX
Power Consumption	5.5 Watts (Maximum)
Speed	10/20Mbps for Half/Full-Duplex 100/200Mbps for Half/Full-Duplex
Media Interface	2*RJ-45, 1*SC
Forwarding Rate	148,800pps
Fiber Mode	Simplex
Cable	10 Base-T 2-Pair Cat-3, 4 to 100mtr (328ft) 100 Base-TX 4 Pair UTP/STP Cat-5(or above) to 100mtr (328ft) EIA/TIA-568 100Ω 10/100 Base-FX 9/125μm single-mode single fiber optic cable upto 20km
Weight	640g
Power	Input 100-240Vac / Freq. 50/60Hz Output 5V DC (1A)
Dimensions	L92 x W71 x H26 mm
Operating Temperature	-0°C~ 70°C
Storage Temperature	-40°C ~80°C
Humidity	5~90%, non-condensing
Emissions	FCC part 15 Class A, CE Mark

Specifications are subject to change without prior notice with advancement in technology.