

GP-U80300I

BayLan Innovation, High Quality Thermal Printer Multi Interface



FEATURES

- Print speed: 300mm/sec. (max.)
- Direct Thermal line and 203dpi
- ESC/POS & STAR command sets compatible
- Built-in WebConfig page make Ethernet setting more conveniently through IE.
- All-in one Serial, USB, 100M Ethernet Interface
- 100M Network interface card make connection and print more faster
- Support two-dimensional barcode printing function (Optional)
- Built-in large data buffer to receive and store printing data
- Characters can be enlarged, bold, underlined, character line spacing can be adjusted
- Support different density bitmap and graphics printing
- Windows driver Linux driver , OPOS driver
- Cash drawer connection port (RJ11)
- Available with plenty of fonts
- Support network status monitoring and PC multi-link printing
- Print density: 576 dpi
- Print head life: >150km
- Dimension : 181mm(L) x 139mm(W) x 127mm(H)

Specifications are subject to change without prior notice with advancement in technology.

SPECIFICATIONS

Print method	Direct Thermal line
Print speed	300mm/sec. (max.)
Print Resolution	512/576 dots/line (203dpi)
Print Width	64/76mm
Paper Width	58 ~ 80.5mm
Paper Diameter	83mm
Line Space	3.75mm(can be adjustable)
Interface	Serial, USB, Ethernet Interface
Character Size	ANK Font Font A: 12 x 24 dots Font B: 9 x 17 dots Simplified/Traditional Chinese character:24x24 dots
Code page	95 Alphanumeric, 48 International, 128x11Graphs PC437/Katakana/PC850/PC860(Portuguese)PC863/ PC865/West Europe/Greek/Hebrew/East Europe/Iran/ WPC1252(ISO8859/2/7/15)/PC866/PC852/PC858/IranII/ PC851/PC853/Page255/Latvian/Arabic/PT151, 1251/ PC737/WPC/1257/Thai Vietnam/PC862/PC1001/ (Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/ (Vietnam)/(Thai)/(PC3847ABNT)/(PC3848ABICOMP) And more
Barcode Type	UPC-A/UPC-E/ JAN 13(EAN13)/JAN8/(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128/GS1/QR CODE/PDF417
Barcode Fonts	GB18030
Buffer Data	128K bytes / NV Flash 256K bytes
Power supply	DC 24V / 2A
Auto-Cutter	Full or partial
Reliability	>150km
Environment	Operating : 0°C ~ +45°C, 10% RH ~ 80% RH Storage : -10°C ~ +60° C, 10% RH ~ 90% RH
Weight	1.23Kg
Dimensions	181mm(L) x 139mm(W) x 127mm(H)

Specifications are subject to change without prior notice with advancement in technology.