PRP-088III
Splash and Dust Proof
Thermal Receipt Printer



PRP-088III high-quality, low-noise thermal receipt printer speed upto 250mm/sec., which is ideal for retail environment. In addition to the horizontal printing, this printer supports vertical and wall mount printing. The splash and dust proof design makes this printer capable for withstanding harsh environment.

FEATURES

- Halt-on protect function for overheat
- Print speed: 250mm/sec. (max.)
- Available with serial,parallel,USB and Ethernet interfaces
- Cash drawer connection port (RJ11)
- Compatible with ESC/POS commands sets
- Splash and dust proof design
- Support vertical printing and wall mount printing
- Drop-and-print paper installation, simple paper jam elimination
- Available with plenty of fonts
- Support OPOS driver
- Support kitchen printing and network printing
- Print and error alarm function. Paper end detection
- Built-in 128K bytes data buffer
- Print Resolution: 576 dots/line or 512 dots/line
- Print head life: 100km (or 52,000,000 lines)
- Dimension : 197mm(L) x 140mm(W) x 143mm(H)

SPECIFICATIONS

Print method	Thermal line Printing
Print speed	250mm/sec. (max.)
Print Resolution	576 dots/line or 512 dots/line
Character Size	ANK Font Font A: 12 x 24 dots Font B: 9 x 17 dots Chinese character:24x24 dots
Interface	Parallel/Serial/USB/Ethernet
Paper Width	79.5mm ± 0.5mm
Paper Roll Diameter	83mm
Paper Thickness	0.06~0.08mm
Power supply	DC 24V / 2.5A
Driver	Win 9X/Win ME/Win 2000/Win 2003/ Win NT/Win XP/Win Vista, Compatible with EPSON* and SAMSUNG*
Auto-Cutter	Full or partial
Reliability	100km
Environment	Operating : 0°C~ 45°C,10% ~ 80%RH Storage : -10°C ~60°C,10% ~90% RH
Weight	1800 g (without Cable)
Dimensions	197mmx (L) x 140mm (W) x 143mm(H)