

PRP-085III

High Speed Thermal Receipt Printer Ethernet Interface



FEATURES

- Halt-on protect function for overheat
- Print speed: 220mm/sec. (max.)
- Available with serial, parallel, USB and Ethernet interfaces
- Cash drawer connection port (RJ11)
- Compatible with ESC/POS commands
- Available with plenty of fonts
- Support OPOS driver
- Print and error alarm function. Paper end detection
- Built-in 128K bytes data buffer
- Print density: 576 dpi
- Print head life: 100km (or 52,000,000 lines)
- Dimension : 199mm(L) x 145mm(W) x 135mm(H)

SPECIFICATIONS

Print method	Thermal line Printing
Print speed	220mm/sec. (max.)
Print Resolution	576 dots/line or 512 dots/line
Character Size	ANK Font Font A: 12 x 24 dots Font B: 9 x 17 dots Chinese character: 24x24 dots
Interface	Parallel/Serial/USB/Ethernet
Paper Width	79.5mm ± 0.5mm
Paper Roll Diameter	83mm
Paper Thickness	0.06~0.08mm
Power supply	Dc 24V / 2.5A
Driver	Win 9X/Win ME/Win 2000/Win 2003/ Win NT/Win XP/Win Vista, Compatible with EPSON and SAMSUNG
Auto-Cutter	Full or partial
Reliability	100km
Environment	Operating : 0°C ~ +45°C, 10% RH ~ 80% RH Storage : -10°C ~ +60°C, 10% RH ~ 90% RH
Weight	1360 g (without Cable)
Dimensions	199mm x (L) x 145mm (W) x 135mm (H)

Specifications are subject to change without prior notice with advancement in technology.