

BZ808-B

High Speed Thermal Receipt Printer

With Queue / Token Printing Function

USB+Serial+Ethernet Interface



FEATURES

- Print speed: 260mm/sec.
- Available with USB+Serial+Ethernet (Network) interfaces
- Auto Cutter
- Cash drawer connection port (RJ11)
- Compatible with ESC/POS commands
- Available with plenty of fonts
- Support OPOS driver
- Print alarm function.
- Print head life: 100km
- Print Density: 504dots/line
- Dimension : 196mm(L) x 145mm(W) x 135mm(H)
- Suitable for Reception, Supermarket and other Applications

Specifications are subject to change without prior notice with advancement in technology.

SPECIFICATIONS

Print method	Thermal line Printing
Print speed	260mm/sec.
Print Resolution	203dpi (576dots/line)
Character Size	Font A: 12 x 24 dots Font B: 9 x 17 dots Chinese character: 24x24 dots
Character Per line	Font A-42 Lines or 48Lines/ Font-B 56 lines or 64lines/ Chinese-21Lines or 24 Lines
Barcode Type	UPC-A, UPC-C, EAN-13, EAN-8, Code 39, ITF, CODABAR, CODE93, CODE128., QR Code,
Paper Width	79.5mm $\pm$ 0.5mm
Printing Width	72mm or 64mm
Paper Reel Diameter	80mm
Paper Thickness	0.06~0.08mm
Paper Loading	Easy Paper Loading
Power supply	Dc 24V / 2.5A
Driver	Win 98 / Win 2000/Win NT/ Win NT / Win XP / OPOS / Win 7 / WIN 8 / Win 10 Compatible with EPSON and SAMSUNG
Auto-Cutter	Full or partial
Reliability	100km
Environment	Operating : 0°C ~ +45°C, 10% RH ~ 80% RH Storage : -10°C ~ +60° C, 10% RH ~ 90% RH
Dimensions	196mmx (L) x 145mm (W) x 135mm(H)
SDK	Android, IOS

Specifications are subject to change without prior notice with advancement in technology.